



cihs



The compact and functional single-phase professional pressure washer

CI H5 is Comac's hot water pressure washer designed to deliver the essential performance professionals need, in a compact, practical, and accessible format.

Equipped with a single-phase induction electric motor with thermal protection, CI H5 is built to handle daily cleaning tasks efficiently, even in demanding environments.

Its solid structure, combined with the vertical boiler with double coil, ensures reliability, resistance, and long-lasting performance. This hot water high-pressure cleaner is a practical and effective solution for cleaning small and medium-sized surfaces in the craft, agricultural, industrial, automotive, and construction sectors, where power and ease of use are essential requirements.

THE ADVANTAGES OF CI H5

Many are the benefits CI H5 can offer:

- Pressure washer equipped with two rear rubber wheels to ensure greater maneuverability and easy transport
- Sturdy and durable handle designed to make transport easier, even on rough terrain
- Reinforced steel base frame and diesel tank made of impact-resistant plastic
- Powerful 2-pole single-phase electric motor with heat protection that makes the pressure washer highly performing, efficient and reliable
- Three hardened stainless steel axial pistons driven by a wobble plate for high-level performance
- Brass pump head with a double seal system for increased durability
- Automatic bypass safety valve with pressure release in the pump head
- Safety pressure switch to turn off the hot box if there is no water inside
- Vertical boiler with double coil to ensure effective and long-lasting heating
- Burner feeding system with screw drive powered by an independent electric motor
- Gear diesel pump driven by an independent electric motor
- Boiler ignition switch with thermostat for water temperature regulation
- Safety valve
- 15-liter fuel oil tank
- Inspectionable water feed filter
- Stop&Go: when the machine is temporarily idle, it stops so as to optimize consumption and reduce waste
- Comes with professional accessories: gun with protection and Swivel coupling, wand with high/low pressure head, foam lance for detergent in low pressure
- 1/4" MEG-type nozzle with 15° flat jet
- 10-meter reinforced high pressure tube
- Hose reel ready



TECHNICAL DESCRIPTION		CI H5
Max pressure	bar/psi	160/2320
Max flow rate	l/h	500
Type	-	cold water
Δ°t	°C	44
Power consumption	KW	2,7
Power supply	V/Hz	230/50
Motor	type/hp	single-phase electric with heat protection
Rotation speed	rpm	2800
Pump	type	with wobble plate (3 hardened stainless steel axial pistons)
Pump head	material	brass
Net weight	Kg	62
Machine dimensions (l x h x w)	mm	720 x 750 x 410



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY
Tel. 045 8774222 - www.comac.it - com@comac.it

Comac S.p.A. org. cert. ISO 9001:2015, ISO 14001:2015, ISO 45001:2018, SA 8000:2014

