



ci c30



The professional three-phase pressure washer with a robust, appealing design

The CI C30 is the three-phase **cold pressure washer** that stands out for its compactness and appealing design. It is also robust, guaranteeing high performance, reliability and durability over time.

Its smaller size manoeuvrability make this **high-pressure washer** extremely comfortable and practical without giving up excellent performance. The CI C30 is also easy to use, thanks to the practical and innovative V-shaped handlebars, which facilitate grip during use.

The CI C30 is the professional **pressure washer** that is perfect for continuous, complex use. Thanks to its innovative technology and its high quality components, it has the ideal high pressure for the cleaning needs of the automotive, industrial, logistics and handicraft sectors.

THE ADVANTAGES OF CI C30

Many are the benefits CI C30 can offer:

- Trolley pressure washer with two large wheels that enhance manoeuvrability and transportability
- New concept ergonomic handlebars with a handlegrip designed to facilitate the use of the pressure washer
- Powerful induction motor that makes the pressure washer highly performing, efficient and reliable
- The low motor rotation speed of only 1450 rpm ensures high durability over time, even during extended sessions
- Ceramic 3-piston pump with crank-rod system and brass head for high performance
- Automatic safety valve with pressure shut-off at pump head
- Three-phase electric induction motor with heat protection that guarantees maximum efficiency and durability
- Adjustable pressure
- Built-in manometer
- Built-in adjustable detergent suction
- Inspectionable water feed filter
- Stop&Go: when the machine is temporarily idle, it stops so as to optimize consumption and reduce waste
- Comes with professional accessories: gun with protection and Swivel coupling, lance with interchangeable nozzle
- 10-metre reinforced high pressure tube
- Built-in accessory holder on machine



TECHNICAL DESCRIPTION		CI C30
Max pressure	bar/psi	230/3300
Max flow rate	l/h	900
Type	-	cold water
Power consumption	KW	7,4
Power supply	V/Hz	400/50
Motor	type	three-phase electric induction
Rotation speed	rpm	1450
Pump	type	ceramic piston with crank-rod system
Pump head	material	brass
Net weight	Kg	52,2
Machine dimensions (Lxhxw)	mm	800x980x470



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY
Tel. 045 8774222 - www.comac.it - com@comac.it

Comac S.p.A. org. cert. ISO 9001, ISO 14001, ISO 45001, SA 8000, ISO 14064-1

