



ci h10



The professional single-phase pressure washer with a vertical hot box and robust, solid structure

The CI H10 is a professional hot pressure washer equipped with a single-phase electric motor capable of guaranteeing excellent performance in more difficult environments. Equipped with a solid, robust structure, this high-pressure washer was designed for professional use. However, the CI H10 is also very compact and easy to handle, thanks to the two back wheels with rubber treads and the pivoting front wheel.

One of the CI H10's key features is the painted steel vertical hot box equipped with a spiral cooling system for the heater, which is switched on by a separate electric motor.

Thanks to the combination of power, pressure and flow rate, this professional hot pressure washer is perfect for deep cleaning environments in the automotive, handicraft, industrial, building and agricultural sectors.

THE ADVANTAGES OF CI H10

Many are the benefits CI H10 can offer:

- Pressure washer with two large back wheels with rubber treads and a front pivoting wheel that facilitate manoeuvrability and transportability
- Practical ergonomic handle to facilitate movement
- Powerful single-phase electric motor with heat protection that makes the pressure washer highly performing, efficient and reliable
- Ceramic 3-piston pump with crank-rod system and brass head for high performance
- Automatic safety valve with pressure shut-off at pump head
- Painted steel vertical hot box equipped with a spiral cooling system for the heater, which is switched on by a separate electric motor, double coil and fireproof cement
- Safety pressure switch to turn off the hot box if there is no water inside
- Time delay panel to switch off the hot box
- Adjustable pressure
- Thermostat
- 22-litre fuel oil tank with drain plug
- Built-in detergent suction
- Practical built-in 3.5/4-litre detergent tank
- Inspectionable water feed filter
- 10-metre reinforced high pressure tube
- Stop&Go: when the machine is temporarily idle, it stops so as to optimize consumption and reduce waste
- Comes with professional accessories: high pressure spray gun, wand with high/low pressure head, reinforced tube
- 1/4" MEG nozzle



TECHNICAL DESCRIPTION		CI H10
Max pressure	bar/psi	150/2200
Max flow rate	l/h	600
Type	-	hot water
Power consumption	KW	3,0
Power supply	V/Hz	230/50
Motor	type	single-phase electric with heat protection
Rotation speed	rpm	1450
Pump	type	ceramic piston with crank-rod system
Pump head	material	brass
Net weight	Kg	82
Machine dimensions (lhxwxh)	mm	1000x820x570



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY
Tel. 045 8774222 - www.comac.it - com@comac.it

Comac S.p.A. org. cert. ISO 9001, ISO 14001, ISO 45001, SA 8000, ISO 14064-1

