



ci h30



The professional three-phase pressure washer with a vertical hot box and robust, solid structure

The CI H30 professional hot pressure washer is equipped with a three-phase electric motor to guarantee excellent performance, even in more difficult environments. Featuring a compact, solid and robust structure, it is a high-pressure washer that is perfect for intensive professional use. The back wheels with rubber treads and the front pivoting wheel also make the CI H30 very easy to manage.

The CI H30's painted steel vertical hot box is equipped with a spiral cooling system for the heater and is switched on by a separate electric motor. It also has a double coil and base made of fireproof cement.

The combination of power, pressure and flow rate of this professional pressure washer gives it durability over time, even if used intensely. Because of this, the CI H30 is the ideal solution for cleaning in the handicraft, industrial, automotive, building and agricultural sectors.

THE ADVANTAGES OF CI H30

Many are the benefits CI H30 can offer:

- Pressure washer with two large back wheels with rubber treads and a front pivoting wheel that facilitate manoeuvrability and transportability
- Practical ergonomic handle to facilitate movement
- Powerful three-phase electric motor with heat protection that makes the pressure washer highly performing, efficient and reliable
- Ceramic 3-piston pump with crank-rod system and brass head for high performance
- Automatic safety valve with pressure shut-off at pump head
- Painted steel vertical hot box equipped with a spiral cooling system for the heater, which is switched on by a separate electric motor, double coil and fireproof cement
- Safety pressure switch to turn off the hot box if there is no water inside
- Time delay panel to switch off the hot box
- Adjustable pressure
- Thermostat
- 22-litre fuel oil tank with drain plug
- Built-in detergent suction
- Practical built-in 6-litre detergent tank
- Inspectionable water feed filter
- Stop&Go: when the machine is temporarily idle, it stops so as to optimize consumption and reduce waste
- Comes with professional accessories: gun with protection and Swivel coupling, wand with high/low pressure head
- 1/4" MEG type nozzle with flat jet
- 10-metre reinforced high pressure tube



TECHNICAL DESCRIPTION		CI H30
Max pressure	bar/psi	190/2800
Max flow rate	l/h	780
Type	-	hot water
Power consumption	KW	5,0
Power supply	V/Hz	400/50
Motor	type	three-phase electric with heat protection
Rotation speed	rpm	1450
Pump	type	ceramic piston with crank-rod system
Pump head	material	brass
Net weight	Kg	85
Machine dimensions (lxhwx)	mm	1000x820x570



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY
Tel. 045 8774222 - www.comac.it - com@comac.it

Comac S.p.A. org. cert. ISO 9001, ISO 14001, ISO 45001, SA 8000, ISO 14064-1

